

The effect of soluble surfactants on liquid film flow

A. Georgantaki¹, M. Vlachogiannis², V. Bontozoglou¹

1. Transport Processes & Process Equipment Laboratory, Department of Mechanical Engineering, University of Thessaly, GR-38334 Volos, Greece
2. Technological Educational Institute of Larissa, GR-41110 Larissa, Greece

We investigate the modifications in the dynamics of liquid film flow, resulting from the addition of soluble surfactants. We use aqueous solutions of iso-propanol (IP) and of sodium dodecyl sulfate (SDS), and perform experiments in two inclined flow facilities, a 3000 mm long by 450 mm wide channel and a 800 mm long by 250 mm wide channel. Both facilities may operate with adjustable width up to the above maximum values. Regular disturbances with frequency in the range 0.15-1.50 Hz are introduced at the inlet, and their temporal evolution at various downstream locations is recorded by conductance probes.

Recent experiments¹ indicate that, unlike classical predictions based on Squire's theorem, the primary instability of film flow in channels of finite width depends on surface tension. Using IP solutions of varying concentrations, we have shown² that this dependence scales with Kapitza number, which expresses the ratio of capillary to viscous stresses. Based on the high solubility and diffusivity of iso-propanol in water, we argue that these solutions behave as pure liquids with reduced surface tension³. Indeed, low-frequency inlet disturbances turn in the unstable regime into solitary humps preceded by capillary ripples, as predicted by theory for simple liquids⁴. The characteristics of these coherent structures correlate satisfactorily with the reduced Reynolds number, $\delta = Re^{11/9} 5Ka^{1/3} 3^{7/9}$.

Aqueous solutions of SDS exhibit a remarkably different behavior, with more pronounced feature the strong damping of all inlet disturbances. In particular, the typical for simple fluids steepening and acceleration of wave crests (which is arrested by the development of front-running capillary ripples and leads to viscous solitary waves) is never observed even at very high Re. The dominant structures for almost the entire range of inlet frequencies tested are sinusoidal traveling waves of very small amplitude. The characteristics of these waves are documented, and are interpreted in terms of the visco-elastic properties of the surfactant monolayer, and in particular the dilational surface elasticity. Though most relevant wavelengths are in the gravity regime, the effect of the surface layer is critical, as has already been shown in a different context⁵.

- (1) Vlachogiannis, M., Samandas, A., Leontidis, V. and Bontozoglou, V. Effect of channel width on the primary instability of inclined film flow. *Phys. Fluids* 2010, 22, 012106.
- (2) A. Georgantaki, J. Vatteville, M. Vlachogiannis and V. Bontozoglou, Measurements of liquid film flow as a function of fluid properties and channel width: Evidence for surface – tension – induced long – range transverse coherence, *Physical Review E*, 2011,84
- (3) Lucassen-Reynders, E. H., Lucassen, J. Properties of Capillary waves. *Advances in Colloid and Interface Science*. 1970, 2, 347.
- (4) H.-C. Chang and E.N. Demekhin, *Complex Wave Dynamics on Thin Films* (Elsevier, Amsterdam, 2002)
- (5) Lucassen, J. Effect of Surface – Active Material on the Damping of Gravity Waves: A Reappraisal. *Journal of Colloid and Interface Science*. 1982,85, 52.

